



PVE 55 DR

www.pvepiling.com

PVE Piling and Drilling Rigs


Powerful, Versatile and Efficient

Impressive torque, **powerful pull down**, with tier IV engine, main lift available, 250 kNm torque

Member of the **DIESEKO GROUP**

PVE 55 DR

PVE is continuously improving their range of equipment. Developments in relation to emission standards and fuel efficiency might result in different specifications. No rights can be attached to the dimensions and specifications mentioned on this leaflet because they might have changed without further notification. All data is subject printing and conversion errors.



All dimensions are in millimeters

Technical specifications PVE 55 DR

Maximum torque	25 ton/mtr (108,496 ft/lbs)
Capacity main winch	10.0/12,5 ton (22047/27557 lbs)
Capacity pull-down winch	6,0 ton (13,227 lbs)
Capacity aux. Winch	3,0 ton (6,614 lbs)
Diesel engine	Caterpillar C-13
Output diesel engine	475 HP
Emission regulation	TIER 3/4
Max. leader length	27,8 mtr
Hydraulic system	Open loop
Hydraulic pumps	Rexroth

Hydraulic valve blocks	Rexroth
Transport width	3.450 mm (11.32ft)
Transport length	19.300 mm (63.32ft)
Transport height	3.585 mm (11.76ft) (incl. RH-15)
Operational length	28.300 mm (92.85ft)
Max. drill length	25.000 mm (82.02ft)
Stroke sliding brace	1.500 mm (4.92ft)
Inclination angel	18.4°
Weight base machine	55,0 ton (121,255 lbs)
Recommended rotary head	PVE RH-25

PVE Piling and Drilling Rigs B.V. Everdenberg 17 4902 TT Oosterhout The Netherlands
T +31 (0)184 - 425 949 F +31 (0)184 - 424 820 I www.pvepiling.com E info@pvepiling.com

027PVE14